

RJ45 Series - Panel Connectors

TECHNICAL SPECIFICATIONS

Material:	
Contacts:	Copper Alloy w/Gold Plate
Connector Body:	PBT (Jack) or PC (Plug)
Operating Temperature:	-20°C to +80°C
Waterproof Rating	IP67 or IP68
Durability:	500 Cycles
Flame Test:	UL / CSA FT4
Thermal Shock:	5 cycles at -20°C to +80°C
Salt Spray:	48 hours



Circular Panel Connectors



Picture:	Type:	Lock Style:	Category:	Name:	Part No:
1	Unshielded Panel Jack	Bayonette	Cat 5e	RJ-5EPFFP-LC7001	2640-0105-01
1	Shielded Panel Jack	Bayonette	Cat 5e	RJS-5EPFFP-LC7001	2640-0105-11
2	Unshielded Panel Jack	Screw Nut	Cat 5e	RJ-5EPFFD-SC7001	2640-0101-01
3	Unshielded Panel Jack	Screw Nut	Cat 5e	RJS-5EPFFJ-SC7001	2640-0103-03
4	Shielded Panel Jack	Screw Nut	Cat 5e	RJS-5EPFFJ-SC7002	2640-0103-02
4	Shielded Panel Jack	Screw Nut	Cat 5e	RJS-5EPFFJ-SC7003*	2640-0103-04
5	Shielded Panel Jack	Screw Nut	Cat 5e	RJS-5EPFFD-SC7001	2640-0107-01
5	Shielded Panel Jack	Screw Nut	Cat 6	RJS-06PFFD-SC7001	2640-0107-02

* Including Earth Wire

Square Panel Connectors



Picture:	Type:	Lock Style:	Category:	Name:	Part No:
1	Unshielded Panel Jack	Screw Nut	Cat 5e	RJ-5EPFFD-SS7001	2640-0106-01
1	Unshielded Panel Jack	Screw Nut	Cat 6	RJ-06PFFD-SS7001	2640-0106-02
2	Shielded Panel Jack	Screw Nut	Cat 5e	RJS-00PFFR-SS7001	2640-0104-01
3	Shielded Panel Jack	Screw Nut	Cat 5e	RJS-5EPFFD-SS7002	2640-0102-01
4	Shielded Panel Jack	Screw Nut	Cat 5e	RJS-5EPFFJ-SS7001	2640-0103-01
5	Shielded Panel Jack	Screw Nut	Cat 5e	RJS-5EPFFD-SS7001	2640-0107-03
5	Shielded Panel Jack	Screw Nut	Cat 6	RJS-06PFFD-SS7001	2640-0107-04