





Verpackt im Gurt nach DIN IEC 60286-3
 Tape on Reel Packaging according to DIN IEC 60286-3
 Verpackungseinheit: 280 Stück
 Packaging unit: 280 pcs




Abspulrichtung - Reel off Direction



Leiterplatten-Layout Vorschlag für SMT
 PCB-Layout Proposal for SMT

Anforderungsstufe 1
 Performance Level 1
 Kontaktbereich vergoldet
 Mating Area gold plating
 Anschlussbereich verzinkt 4-6 µm
 Terminal Area 4-6 µm tin plating
 Koplanarität der Anschlüsse ≤ 0.1 mm
 Coplanarity Area of Termination ≤ 0.1 mm



BA 7-13 - 8mm Bauhöhe
 type7-13 - Low Profile

Information:	Tolerances	 All Dimensions in mm	Scale	3:1
	All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Designation Federl. SMC-B 50-SMD-BA7-13 <i>Female SMC-B 50-SMD-type7-13</i>	
Subject to modification without prior notice. Drawing will not be updated.		www.ERNI.com		154807
e	14.01.2014	Date		I
Index		Class		A3
				SMCB

Copyright by ERNI GmbH
 Proprietary notice pursuant to ISO 16018 to be observed.