

High frequency ground wire choke, shrink hose



Description

- Ground wire chokes (earth line chokes)
- Wire leads

Standards

- EN 60938

Applications

- Separating the main earth line to periphery devices
- This type of chokes permits the building of a system free of ground wire loops

References

Weblinks

General Product Information, Approvals, RoHS, CHINA-RoHS, e-Store, SCHURTER-Stock-Check, Distributor-Stock-Check

Technical Data



Rated Current	16 - 25A @ Ta 40 °C
Rated inductance	0.02 - 4mH, Tol. ±15%
Power Operating Frequency	> 5MHz
Terminal technic	Wire leads
Weight	17 - 51 g
Material: Housing	UL 94V-0
Sealing Compound	UL 94V-0

Isolation Voltage	2 kV eff., winding to ambient
Climatic Category	25/100/21 acc. to IEC 60068-1
Allowable Operation Temp.	-25 °C to 100 °C


Dimensions

16A

25A



Diagrams



Example of a perfect earth line system using a radiator and an earth line choke

Variants

I_n [A]	L_n [mH]	R_{Cu} [mΩ]	f_{RES} [MHz]	Weight [g]	Packing unit [pcs.]	Order Number
16	0.02	15	30	17	100	DEHL-10-0001
25	0.04	10	20	51	50	DEH-15-0001