

RoHS Compliant

Material & Finishes

Insulator : PBT, UL 94V-0
 Contact : Brass, Gold flash plated on mating area
 Sn plated on soldertails
 Nickel under plated overall
 Shell : SPCC, Nickel plated
 Rivet : Copper alloy, Nickel plated
 Board lock : Copper alloy, Sn plated
 Screw : SPCC or Copper alloy, Nickel plated

Specification

Current rating : 1 Amp max.
 Insulation Resistance : 1,000 Mohm min. at DC 500V
 Contact resistance : 30 mOhm max.
 Dielectric withstanding voltage : 500V AC for 1 minute
 Operation temperature : - 55°C ~ + 105°C

Dimensions


Contact	A	B	C
09	16.92	24.99	30.81
15	25.25	33.32	39.14
25	38.96	47.04	53.04
37	55.42	63.50	69.32

Order Information

DR - 00 F X X


*** Options:**

- Put (01), or (02), or others on end of P/N
- * Contacts plating: G = full, S = selective gold
- * Insulator color / shell plating:
 D - Black/Tin, E - Black/Nickel
- * Poles: 09, 15, 25, 37, 50




Standard

Options :



(01) - #4-40 Rivted
Screws optioned



(02) - #4-40 Rivted
Screws locked

