



Recommend PCB Layout



Material :

Insulator : 30% Glass Fiber PBT, UL 94V-0
 Contact : Copper alloy, Gold flash plated

Specification :

Current Rating : 3 Amp
 Voltage Rating : 250V AC/DC
 Insulation Resistance : 1,000 Mohm min. at DC 500V
 Contact Resistance : 20 mOhm max.
 Withstanding Voltage : 500V AC for 1 minute
 Operation Temperature Range : - 40°C ~ + 105°C

Order Information

PH - 1x 00 R G 2

- * Type
 - Type 1: A = 6.0, B = 3.0, C = 1.5mm
 - Type 2: A = 6.0, B = 3.0, C = 4.54mm
- * Contacts plating
 - G - full gold flash
 - S - Selective gold flash
- * R - Right Angle
- * Contacts No. - 02 ~ 40

* For special length of contacts, put the length (mm) for (A / B / C) required at end of P/N, to instead of (X)

E				Drawn:	General Tolerance			<i>Useconn Electronics Ltd.</i>	
D				David Chang	.0	.00	.000		
C				Checked:	± 0.30	± 0.20	± 0.10	Title : 2.54mm pitch Pin Header Strip R/A, Single row	
B				Ivy Lee	Unit : mm				
A	18-May-10	new release	David	Appraisal:	Scale :			Part No. PH - 1 x 00 RG	File No. :
Rev.	Date	File	BY	Simon Chen	Sheet : 1/1				